



PoE World

World Class
Injectors Switches Splitters
Extenders Testers

Our Locations and Partners :

PoE-Texas Austin Texas

Amazon UK/EU

PoE-World Shenzhen China

<http://poe-world.com>

ZQ-P3020C

30 Watt

In Wall USBC PSE
for 86x86 mm

Auto Negotiates

ETL listed



[Product Description – ZQ-P3020C USBC power adapter for Euro boxes](#)

This device provides an embeddable solution for delivering power to a USBC device.

Intended for use with any USBC device, this active PSE solution negotiates with the USBC device to activate power at the proper level. It is a compact and cost effective power solution. The input is typically 240 VAC, 50 Hz., however operation at 120vac is also supported.

Use a Right Angle USB-C connector is recommended.

[Specifications](#)

Power source	Brown / Blue wires
Input Voltage	100 – 240 VAC, 50/60 Hz
Power Factor	0.50 @ 5 watts
Internal Power usage in standby	0 mW
Operating Temperature	0°C ~ 50°C
Size	49 x 50 x 27 mm Fits into 86x86 box
Weight	3.5 ounces
Isolation	Isolated – 1500 volt class II isolation



Optional RA USB-C Cable

USBC
Voltage
5.0 V
9.0 V
12 V
15 V
20 V

Output Current and Watts
3.0 Amps | 15 Watts
3.0 Amps | 27 Watts
2.5 Amps | 30 Watts
2.0 Amps | 30 Watts
1.5 Amps | 30 Watts

