

### PoE World

World Class
Injectors Switches Splitters
Extenders Testers

### Our Locations and Partners:

PoE-Texas Austin Texas
Amazon UK/EU
PoE-World Shenzhen China

http://poe-world.com

# **ZQ-P3020C**

30 Watt

In Wall USBC PSE for 86x86 mm

**Auto Negotiates** 

## **ETL listed**



### <u>Product Description – ZQ-P3020C USBC power adapter for Euro boxes</u>

This device provides an embeddable solution for delivering power to a USBC device.

Intended for use with any USBC device, this active PSE solution negotiates with the USBC device to activate power at the proper level. It is a compact and cost effective power solution. The input is typically 240 VAC, 50 Hz., however operation at 120vac is also supported.

Use a Right Angle USB-C connector is recommended.

#### **Specifications**

Power source Brown / Blue wires
Input Voltage 100 - 240 VAC, 50/60 Hz
Power Factor 0.50 @ 5 watts
Internal Power usage in standby 0 mWOperating Temperature  $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ 

Operating Temperature  $0^{\circ}\text{C} \sim 50^{\circ}\text{C}$ Size  $49 \times 50 \times 27 \text{ mm}$ Weight 3.5 ounces

Isolation Isolated – 1500 volt class II isolation



Optional RA USB-C Cable

Output Current and Watts
3.0 Amps   15 Watts
3.0 Amps   27 Watts
2.5 Amps   30 Watts
2.0 Amps   30 Watts
1.5 Amps   30 Watts

