



PoE World

World Class
Injectors Switches Splitters
Extenders Testers

Our Locations and Partners :

USA: PoE-Texas Austin Texas
UK/EU/ROW: PoE-World Shenzhen China

<http://poe-world.com>

AC-USBC2

60 Watt

Dual In Wall USBC PSE

Auto Negotiation

ETL listed



Product Description – ZQ-P0602C Dual USBC power adapter for Euro boxes

This device provides an embeddable solution for delivering power to a USBC device.

Intended for use with any USBC device, this active PSE solution negotiates with the USBC device to activate power at the proper level. It is a compact and cost effective power solution. The input is typically 120-240 VAC, 50/60 Hz.

Use a Right Angle USB-C connector is recommended.

Specifications

Power wiring colors	Brown / Blue wires	14.5 cm
Input Voltage	100 – 240 VAC,	50/60 Hz
Power Factor	0.50 @ 5 watts	
Internal Power usage in standby	0 mW	
Operating Temperature	0°C ~ 50°C	
Size	63 x 51 x 31 mm	Fits into 86x86 box
Weight	5.5 ounces	
Isolation	Isolated – 1500 volt class II isolation	



Optional RA USB-C Cable

USBC Voltage	Output Current and Watts 1 load	Output Current and Watts 2 loads
5.0 V	3.0 Amps 15 Watts	3.0 Amps 15 Watts
9.0 V	3.0 Amps 27 Watts	3.0 Amps 27 Watts
12 V	3.0 Amps 36 Watts	2.5 Amps 30 Watts
15 V	3.0 Amps 45 Watts	2.0 Amps 30 Watts
20 V	3.0 Amps 60 Watts	1.5 Amps 30 Watts

